




PRI Filler/Primer Gun




GTI Pro Topcoat Gun




GTI Pro Topcoat Gun



GTI Pro Topcoat Gun




SRI Pro Spot Repair Gun




SRI Pro Spot Repair Gun

Air Cap No & Technology:		P1 (Trans-Tech)	H1 (HVLP)	T1 (Trans-Tech)	T2 (Trans-Tech)	HS1 (HVLP)	TS1 (Trans-Tech)
SPRAY POLYESTER	P565-2901 Polyester Filler	2.0-2.5 mm	Use PRi	Use PRi	Use PRi	Use PRi	Use PRi
PRIMERS	P565-9850 Chromate Free Etch Primer	1.6 mm	Use PRi	Use PRi	Use PRi	0.8 mm	0.8 mm
	P565-3030/1 Fast Wet-on-Wet Primer	Do Not Use	Do Not Use	1.3 mm	1.3 mm	Use SRi	0.8 mm
	P565-357/8 Wet-on-Wet Primer	Do Not Use	Do Not Use	1.3 mm	1.3 mm	Use SRi	0.8 mm
	P565-5301/5/7 High Build Filler / Surfacer	1.6 mm	Use PRi	Use PRi	Use PRi	Do Not Use	1.0 mm
	P565-888/9 High Build Filler / Surfacer	1.6 mm	Use PRi	Use PRi	Use PRi	Do Not Use	1.0 mm
	P565-4505/4507 Primer Filler as a Filler	1.8 mm	Use PRi	Use PRi	Use PRi	Do Not Use	1.0 mm
	P565-4505/4507 Primer Filler as a Surfacer	1.6 mm	Use PRi	Use PRi	Use PRi	Do Not Use	1.0 mm
	P950-2028 Waterborne Epoxy Primer	Do Not Use	Do Not Use	1.3 mm	1.3 mm	Use SRi	0.8 mm
SOLID COLOUR	P471-2K HS+ High Solid Colour	Do Not Use	1.2 - 1.3 mm	1.2 - 1.3 mm	1.2 - 1.3 mm	0.8 mm	0.8 mm


SPRAY GUN SET UP SELECTOR: Gun Inlet Pressure 2.0 bar or as stated




PRI Filler/Primer Gun




GTI Pro Topcoat Gun




GTI Pro Topcoat Gun



GTI Pro Topcoat Gun



SRi Pro Spot Repair Gun



SRi Pro Spot Repair Gun

Air Cap No & Technology:		P1 (Trans-Tech)	H1 (HVLP)	T1 (Trans-Tech)	T2 (Trans-Tech)	HS1 (HVLP)	TST (Trans-Tech)
BASECOAT	P422 Basecoat Solventborne Basecoat	Do Not Use	1.2 - 1.3 mm	1.2 - 1.3 mm	1.2 - 1.3 mm	0.8 mm	0.8 mm
	P965- Aquabase/ Aquabase Plus Waterborne Basecoat	Do Not Use	1.2 - 1.3 mm	1.2 - 1.3 mm	1.2 - 1.3 mm	0.8 mm	0.8 mm
CLEARCOATS	P190-6680 HS+ Clearcoat	Do Not Use	Do Not Use	1.2 - 1.3 mm	1.2 - 1.3 mm	0.8 mm	0.8 mm
	P190-6690 HS+ Clearcoat	Do Not Use	Do Not Use	1.2 - 1.3 mm	1.2 - 1.3 mm	0.8 mm	0.8 mm
	P190-6659 HS+ Express Clearcoat	Do Not Use	Do Not Use	1.2 - 1.3 mm	1.2 - 1.3 mm	0.8 mm	0.8 mm
	P190-6698 Low VOC Clearcoat	Do Not Use	Do Not Use	1.2 - 1.3 mm	1.2 - 1.3 mm	0.8 mm	0.8 mm